

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61F 13/15		(11) International Publication Number: WO 98/33463
A1		(43) International Publication Date: 6 August 1998 (06.08.98)
(21) International Application Number: PCT/SE98/00187		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GI, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).
(22) International Filing Date: 3 February 1998 (03.02.98)		
(30) Priority Data: 9700371-9 4 February 1997 (04.02.97) SE		
(71) Applicant (for all designated States except US): SCA MÖLNLYCKE AB [SE/SE]; S-405 03 Göteborg (SE).		
(72) Inventor; and (75) Inventor/Applicant (for US only): WIDLUND, Urban [SE/SE]; Pärönvägen 5, S-435 43 Pixbo (SE).		
(74) Agents: GRAUDUMS, Valdis et al.; Albinns Patentbyrå Göteborg AB, P.O. Box 142, S-401 22 Göteborg (SE).		Published With international search report.

(54) Title: ABSORBENT ARTICLE HAVING IMPROVED SURFACE PROPERTIES

(57) Abstract

An absorbent article, such as a sanitary napkin, a panty-liner or an incontinence protector, comprising a liquid-pervious surface layer (2), a liquid-impervious surface layer (3), and an absorbent body (4) enclosed between the two surface layers (2, 3), wherein the article further exhibits a wetting region (15), which is the region of the liquid-pervious surface layer which is intended to first be wetted by body fluid emitted to the article. The liquid-pervious surface layer (2) is constituted of a hydrophilic material (16) within the wetting region (15), at least at the surface of the layer (2) which is intended to be facing the user during use. The remaining parts of the liquid-pervious surface layer (2) are constituted of a hydrophobic material (14).

